

DS-K1T804 Series Fingerprint Access Control Terminal



Available Models

DS-K1T804F (Fingerprint) DS-K1T804EF (EM Card, Fingerprint) DS-K1T804MF (M1 Card, Fingerprint)

Features

- Person information structure: based on employee ID
- Supports 6 attendance status, including check in, check out, break in, break out, overtime in, overtime out
- Supports multiple languages: English, Vietnamese, Brazilian Portuguese, Spanish, French, Italian, Arabic, and Thai
- Accesses to public network via EHome 4.0 or 5.0 protocol, and sets EHome parameters on the client or device
- Integrated management of access control and the attendance
- 2.4-inch LCD screen to display the time, the date and swiping/fingerprint authentication results
- Remotely registers fingerprints from the terminal to software
- Max. 3000 users, Max. 3000 fingerprints and Max. 100,000 event records
- Two attendance authentication modes: authentication by person, authentication by device
- Stand-alone operation: locally add person, card and fingerprint information
- Exports the swiping card data and the attendance report to the USB flash drive
- Up to 32 normal shifts and up to 32 man-hour shifts can be configured
- Up to 32 attendance holiday schedules and up to 128 access control holiday schedules can be configured
- Generates the attendance report automatically and view the attendance data easily
- The third party bell access
- Tamper alarm and duress alarm function





- Connects the external secure door control unit via RS-485 to avoid the door opening when the terminal is destroyed
- Supports the third party alarm input

Specifications

Model	DS-K1T804F	DS-K1T804MF	DS-K1T804EF	
Operating system	Linux			
Storage	Up to 3000 valid cards; Up to 100,000 event records; Up to 150,000 attendance records			
Fingerprint capacity	Up to 3000 fingerprints; up to 10 fingerprints for each person			
Fingerprint Comparing Mode	1:1 and 1:N, N=3000			
Card reading response duration	<1s			
Fingerprint authentication duration	<1s			
FAR (False Acceptance Rate)	≤ 0.001 %			
FRR (False Rejection Rate)	≤ 0.01 %			
Fingerprint recognizer	Optical fingerprint recognizer module			
External card reader	Standard Wiegand26/34			
Card Reading Distance	/	Supports Mifare card, including cards with special shapes; Supports reading card in metal environment	Supports EM card, including cards with special shapes; Supports reading card in metal environment	
Card reading distance	/	0 to 4.5 cm	0 to 5 cm	
Keypad	Keypad (backlight)			
Reset key	×1			
Communication interface	TCP/IP, RS-485 (for secure door control unit), Wiegand output (W26/W34) and input (Wiegand 26/34)			
Wi-Fi	Support			
Wiegand interface	Output: Wiegand 26/34; Input: Wiegand 26/34			
Transmission rate	TCP/IP: 10/100Mbps, self-adaptive; RS-485: 19200 bps-N-8-1			
Input interface	Exit button × 1, door contact × 1 and alarm input × 1			
Output interface	Relay (lock output) × 1, and alarm output × 1			
USB	USB 2.0; type A			
LCD screen	2.4-inch (320× 240 LCD-TFT display screen)			
Audio	1 buzzer and 1 loudspeaker			
LED indicator	Power/status (red/green)			
Power supply	12 VDC/2 A			
Working temperature	-10 °C to +55 °C (14 °F to +131 °F)			



Model	DS-K1T804F	DS-K1T804MF	DS-K1T804EF	
Working humidity	10% to 90% (no condensing)			
Tamper-proof	Support			
Color	Black (included), gold (optional), silver (optional), white (optional)			
Dimension (L × W × H)	205 mm × 76.5 mm × 37 mm (8.07" × 3.01" × 1.46")			
Installation	Surface mounting, metal door mounting, installation with gang box			

Appearance









Black

Gold

Silver

Distributed by



Headquarters

No.555 Qianmo Road, Binjiang District, Hangzhou 310051, China T +86-571-8807-5998 overseasbusiness@hikvision.com

Hikvision USA T +1-909-895-0400 sales.usa@hikvision.com

Hikvision Australia T +61-2-8599-4233 salesau@hikvision.com

Hikvision India T +91-22-28469900 sales@pramahikvision.com

Hikvision Canada T +1-866-200-6690 sales.canada@hikvision.com

Hikvision Thailand T +662-275-9949 sales.thailand@hikvision.com Hikvision Europe T +31-23-5542770 sales.eu@hikvision.com

Hikvision Italy T +39-0438-6902 info.it@hikvision.com Hikvision Brazil T +55 11 3318-0050

Latam.support@hikvision.com Hikvision Turkey T +90 (216)521 7070- 7074

sales.tr@hikvision.com

T +601-7652-2413 sales.my@hikvision.com Hikvision UK & Ireland T +01628-902140 sales.uk@hikvision.com

Hikvision South Africa Tel: +27 (10) 0351172 sale.africa@hikvision.com

Hikvision France T +33(0)1-85-330-450 info.fr@hikvision.com

Hikvision Kazakhstan T +7-727-9730667 nikia.panfilov@hikvision.ru

Hikvision Vietnam T +84-974270888 sales.vt@hikvision.com Hikvision UAE T +971-4-4432090 salesme@hikvision.com

Hikvision Singapore T +65-6684-4718 sg@hikvision.com

Hikvision Spain T +34-91-737-16-55 info.es@hikvision.com

Hikvision Tashkent T +99-87-1238-9438 uzb@hikvision.ru

Hikvision Hong Kong T +852-2151-1761 info.hk@hikvision.com Hikvision Russia T +7-495-669-67-99 saleru@hikvision.com

Hikvision Korea T +82-{0}31-731-8817 sales.korea@hikvision.com

Hikvision Poland T +48-22-460-01-50 info.pl@hikvision.com

Hikvision Indonesia T +62-21-2933759 Sales.Indonesia@hikvision.com

Hikvision Colombia sales.colombia@hikvision.com

C Hikvision Digital Technology Co., Ltd. 2019 | Data subject to change without notice |